

Declaration of Performance **Pilkington Optifloat Clear** (annealed)

We, **LLC Pilkington Glass**, representing the following:

Manufacturing Plant: 1, Stekolnaya street, Zhukovo village, Ramensky district, Moscow region, 140125, Russian Federation

Herewith declare, under his sole responsibility, the following characteristics for the CE Marking of the soda lime silicate glass intended to be used in buildings and construction works named Pilkington Optifloat Clear (annealed) produced in compliance with *Production Instruction I-4-QA-6101 and EN 579-9 "Glass in Building – Basic soda lime silicate glass products -Part9: Evaluation of conformity/Product standard"* and is in conformity with the provisions of the following EU Regulation when installed under the installation instructions contained in the product documentation: *Regulation (EU) No 305/2011 Construction Products Regulation*.

Declared performance:

Pilkington Optifloat Clear (annealed) characteristics in:	AVCP Systems	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
Resistance to fire	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Reaction to fire	4	A1	A1	A1	A1	A1	A1	A1
External fire performances	3,4	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Bullet resistance	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Explosion resistance	1	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Burglar resistance	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Pendulum body impact resistance	3	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Resistance against sudden temperature change and temperature differentials	4	40 K	40 K	40 K	40 K	40 K	40 K	40 K
Wind, snow, permanent and imposed load resistance	4	45 MPa	45 MPa	45 MPa	45 MPa	45 MPa	45 MPa	45 MPa
Direct airborne sound reduction	3	29 (-1;-4) dB	29 (-2;-3) dB	30(-1;-2) dB	31 (-2;-3) dB	32 (-2;-3) dB	33 (-2;-3) dB	34 (0;-2) dB
Thermal Properties	3	5.8 W/m ² K	5.8 W/m ² K	5.8 W/m ² K	5.7 W/m ² K	5.6 W/m ² K	5.6 W/m ² K	5.5 W/m ² K
Radiation Properties								
-Light Transmittance / Reflectance	3	0.92/0.09/0.09	0.91/0.09/0.09	0.91/0.09/0.09	0.90/0.09/0.09	0.89/0.08/0.08	0.88/0.08/0.08	0.88/0.08/0.08
-Solar Transmittance / Reflectance	3	0.86/0.08/0.08	0.85/0.08/0.08	0.83/0.08/0.08	0.81/0.08/0.08	0.79/0.07/0.07	0.76/0.07/0.07	0.74/0.07/0.07
g value	3	0.88	0.88	0.87	0.86	0.84	0.82	0.80
Durability	3,4	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Normal emissivity	3	0.89	0.89	0.89	0.89	0.89	0.89	0.89

Notified production control certification body number 1694

Maxim Lazutkin
 Technical regulations manager
 Sep 30, 2021

